Obtaining ZnO-Si heterostructures on silicon substrates

Authors

Postgraduate student Ivan Padalka
Professor Igor Virt
Department of Physics and Information Systems,
Ivan Franko Drohobych State Pedagogical University

Introduction

Zinc oxide (ZnO) is a wide-bandgap semiconductor with promising applications in optoelectronics, photovoltaics, and sensor technologies. The integration of ZnO films with silicon (Si) substrates is of particular interest due to the possibility of creating high-performance devices that combine the advantages of both materials. This study reviews the deposition methods, structural properties, and potential applications of ZnO films on silicon and ZnO-Si heterostructures.

Study of heterostructures

ZnO-Si is being actively studied due to its optoelectronic properties. The ZnO/Si interface plays a key role in determining the efficiency of devices, especially in photovoltaic applications. Experimental results indicate that optimizing the deposition parameters allows for improved charge transfer and reduced recombination losses at the interface.

Methodology

ZnO films can be prepared by various methods, including magnetron sputtering, chemical vapor deposition, and pulsed laser deposition. The choice of method affects the crystallinity, morphology, and electronic properties of the resulting films. Studies show that ZnO adheres well to silicon, but the interface states and stresses in the layers must be carefully controlled.

Recent research

Recent advances in pulsed laser deposition and atomic layer deposition have enabled the fabrication of ultrathin ZnO films with highly precise thickness control. These technologies provide excellent film uniformity and high interface quality, making them suitable for advanced nanoelectronic and photonic applications.

Properties for deposition

A critical factor in the deposition of ZnO films is the choice of process parameters, such as substrate temperature, deposition rate, and oxygen partial pressure. These parameters significantly affect the crystallographic orientation, surface roughness, and defect density in the films. Controlled regulation of these conditions ensures the formation of high-quality ZnO layers with minimal defects and improved optoelectronic characteristics.







Conclusions

ZnO-Si heterostructures have significant potential for use in optoelectronics and photovoltaics due to the combination of unique properties of zinc oxide and silicon. It is shown that the choice of the deposition method of ZnO films, as well as the optimization of technological parameters, significantly affect the morphology, crystallinity and electronic characteristics of the structures

References

1. Ü. Özgür et al., J. Appl. Phys., 98, 041301 (2005).
2. C. Klingshirn, Phys. Status Solidi B, 244, 3027-3073 (2007).
3. S.J. Pearton et al., Prog. Mater. Sci., 50, 293-340 (2005).
4. T. Minami, Semicond. Sci. Technol., 20, S35-S44 (2005).

Graphical Characteristics of ZnO/Si Heterostructure